

Pinnacle Impact Series


CLAD AWNING

ELEVATIONS : OPERATING / STATIONARY


SCALE: 1/8" = 1'-0"

	Masonry Opg.	2-0 3/4	2-4 3/4	2-6 3/4	3-0 3/4	3-6 3/4	4-0 3/4
	Rough Opg.	2-0 3/4	2-4 3/4	2-6 3/4	3-0 3/4	3-6 3/4	4-0 3/4
	Frame	2-0	2-4	2-6	3-0	3-6	4-0
	Glass	20	24	26	32	38	44
1-6 1/2							
		2014	2414	2614	3214	3814	4414
1-8 1/2							
		2016	2416	2616	3216	3816	4416
2-0 1/2							
		2020	2420	2620	3220	3820	4420
2-4 1/2							
		2024	2424	2624	3224	3824	4424
2-6 1/2							
		2026	2426	2626	3226	3826	4426
3-0 1/2							
					3232	3832	4432

OPERATION



OTHER GRILLE PATTERN



UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:

MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING