






























Pinnacle Series
DOUBLE HUNG - 16" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	2-0 3/4	3-10 1/8	5-7 1/2
					1-10 1/8	3-7 1/2	5-4 7/8
					1-10 1/8	3-7 1/2	5-4 7/8
					1-9 3/8	3-6 3/4	5-4 1/8
					16	16	16
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	 1614	 1614-2	 1614-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	 1616	 1616-2	 1616-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	 1620	 1620-2	 1620-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	 1622	 1622-2	 1622-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	 1624	 1624-2	 1624-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	 1626	 1626-2	 1626-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	 1628	 1628-2	 1628-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	 1630	 1630-2	 1630-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	 1632	 1632-2	 1632-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	 1634	 1634-2	 1634-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	 1636	 1636-2	 1636-3

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING







NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.

1/21/14

Pinnacle Series
DOUBLE HUNG - 16" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"


Mas. Opg. Primed	2-0 3/4	3-10 1/8	5-7 1/2
Mas. Opg. Clad	1-10 1/8	3-7 1/2	5-4 7/8
Rough Opg.	1-10 1/8	3-7 1/2	5-4 7/8
Frame	1-9 3/8	3-6 3/4	5-4 1/8
Glass	16	16	16

7-2 13/16	7-1 1/4	7-1 1/4	7-0 3/4	38-38	
					
	1638*	1638-2*	1638-3*		
7-6 13/16	7-5 1/4	7-5 1/4	7-4 3/4	40-40	
					
	1640*	1640-2*	1640-3*		

(* CONCEALED JAMBLINER ONLY)

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.


Pinnacle Series
DOUBLE HUNG - 20" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	2-4 3/4	4-6 1/8	6-7 1/2
					2-2 1/8	4-3 1/2	6-4 7/8
					2-2 1/8	4-3 1/2	6-4 7/8
					2-1 3/8	4-2 3/4	6-4 1/8
					20	20	20
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	2014	2014-2	2014-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	2016	2016-2	2016-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	2020	2020-2	2020-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	2022	2022-2	2022-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	2024	2024-2	2024-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	2026	2026-2	2026-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	2028	2028-2	2028-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	2030	2030-2	2030-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	2032	2032-2	2032-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	2034	2034-2	2034-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	2036	2036-2	2036-3

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.


1/21/14


Pinnacle Series
DOUBLE HUNG - 20" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	2-4 3/4	4-6 1/8	6-7 1/2
Mas. Opg. Clad	2-2 1/8	4-3 1/2	6-4 7/8
Rough Opg.	2-2 1/8	4-3 1/2	6-4 7/8
Frame	2-1 3/8	4-2 3/4	6-4 1/8
Glass	20	20	20


7-2 13/16 | 7-1 1/4 | 7-1 1/4 | 7-0 3/4 | 38-38



2038*



2038-2*


2038-3*

7-6 13/16 | 7-5 1/4 | 7-5 1/4 | 7-4 3/4 | 40-40



2040*



2040-2*


2040-3*

(* CONCEALED JAMBLINER ONLY)

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*
































* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.


Pinnacle Series
DOUBLE HUNG - 24" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	2-8 3/4	5-2 1/8	7-7 1/2
					2-6 1/8	4-11 1/2	7-4 7/8
					2-6 1/8	4-11 1/2	7-4 7/8
					2-5 3/8	4-10 3/4	7-4 1/8
					24	24	24
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	 2414	 2414-2	 2414-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	 2416	 2416-2	 2416-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	 2420	 2420-2	 2420-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	 2422	 2422-2	 2422-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	 2424	 2424-2	 2424-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	 2426	 2426-2	 2426-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	 2428	 2428-2	 2428-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	 2430	 2430-2	 2430-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	 2432	 2432-2	 2432-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	 2434	 2434-2	 2434-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	 2436	 2436-2	 2436-3

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.

1/21/14

Pinnacle Series
DOUBLE HUNG - 24" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"


Mas. Opg. Primed	2-8 3/4	5-2 1/8	7-7 1/2
Mas. Opg. Clad	2-6 1/8	4-11 1/2	7-4 7/8
Rough Opg.	2-6 1/8	4-11 1/2	7-4 7/8
Frame	2-5 3/8	4-10 3/4	7-4 1/8
Glass	24	24	24



7-2 13/16 | 7-1 1/4 | 7-1 1/4 | 7-0 3/4 | 38-38

2438* | 2438-2* | 2438-3*


(* CONCEALED JAMBLINER ONLY)



7-6 13/16 | 7-5 1/4 | 7-5 1/4 | 7-4 3/4 | 40-40

2440* | 2440-2* | 2440-3*

OTHER GRILLE PATTERNS



PRAIRIE | PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.

Pinnacle Series
DOUBLE HUNG - 26" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	2-10 3/4	5-6 1/8	8-1 1/2
					2-8 1/8	5-3 1/2	7-10 7/8
					2-8 1/8	5-3 1/2	7-10 7/8
					2-7 3/8	5-2 3/4	7-10 1/8
					26	26	26
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	2614	2614-2	2614-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	2616	2616-2	2616-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	2620	2620-2	2620-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	2622	2622-2	2622-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	2624	2624-2	2624-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	2626	2626-2	2626-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	2628	2628-2	2628-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	2630	2630-2	2630-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	2632	2632-2	2632-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	2634	2634-2	2634-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	2636	2636-2	2636-3

OTHER GRILLE PATTERNS



PRAIRIE



PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*




* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL




NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.

Pinnacle Series
DOUBLE HUNG - 26" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"


	2638*	2638-2*	2638-3*
Mas. Opg. Primed	2-10 3/4	5-6 1/8	8-1 1/2
Mas. Opg. Clad	2-8 1/8	5-3 1/2	7-10 7/8
Rough Opg.	2-8 1/8	5-3 1/2	7-10 7/8
Frame	2-7 3/8	5-2 3/4	7-10 1/8
Glass	26	26	26
7-2 13/16			
7-1 1/4			
7-1 1/4			
7-0 3/4			
38-38			

	2640*	2640-2*	2640-3*
7-6 13/16			
7-5 1/4			
7-5 1/4			
7-4 3/4			
40-40			

(* CONCEALED JAMBLINER ONLY)

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*
































* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 28" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	3-0 3/4	5-10 1/8	8-7 1/2
					2-10 1/8	5-7 1/2	8-4 7/8
					2-10 1/8	5-7 1/2	8-4 7/8
					2-9 3/8	5-6 3/4	8-4 1/8
					28	28	28
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	 2814	 2814-2	 2814-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	 2816	 2816-2	 2816-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	 2820	 2820-2	 2820-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	 2822	 2822-2	 2822-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	 2824	 2824-2	 2824-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	 2826	 2826-2	 2826-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	 2828	 2828-2	 2828-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	 2830	 2830-2	 2830-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	 2832	 2832-2	 2832-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	 2834	 2834-2	 2834-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	 2836	 2836-2	 2836-3

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 28" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	3-0 3/4	5-10 1/8	8-7 1/2
Mas. Opg. Clad	2-10 1/8	5-7 1/2	8-4 7/8
Rough Opg.	2-10 1/8	5-7 1/2	8-4 7/8
Frame	2-9 3/8	5-6 3/4	8-4 1/8
Glass	28	28	28


7-2 13/16 / 7-1 1/4 / 7-1 1/4 / 7-0 3/4 / 38-38



2838*



2838-2*


2838-3*


7-6 13/16 / 7-5 1/4 / 7-5 1/4 / 7-4 3/4 / 40-40



2840*


2840-2*


2840-3*

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

(* CONCEALED JAMBLINER ONLY)

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*
































* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 30" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	3-2 3/4	6-2 1/8	8-11 1/2
					3-0 1/8	5-11 1/2	8-10 7/8
					3-0 1/8	5-11 1/2	8-10 7/8
					2-11 3/8	5-10 3/4	8-10 1/8
					30	30	30
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	 3014	 3014-2	 3014-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	 3016	 3016-2	 3016-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	 3020	 3020-2	 3020-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	 3022	 3022-2	 3022-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	 3024	 3024-2	 3024-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	 3026	 3026-2	 3026-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	 3028	 3028-2	 3028-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	 3030	 3030-2	 3030-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	 3032	 3032-2	 3032-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	 3034	 3034-2	 3034-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	 3036	 3036-2	 3036-3

1/21/14

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL


NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 30" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"

	3038*	3038-2*	3038-3*
Mas. Opg. Primed	3-2 3/4	6-2 1/8	8-11 1/2
Mas. Opg. Clad	3-0 1/8	5-11 1/2	8-10 7/8
Rough Opg.	3-0 1/8	5-11 1/2	8-10 7/8
Frame	2-11 3/8	5-10 3/4	8-10 1/8
Glass	30	30	30
7-2 13/16			
7-1 1/4			
7-1 1/4			
7-0 3/4			
38-38			




	3040*	3040-2*	3040-3*
7-6 13/16			
7-5 1/4			
7-5 1/4			
7-4 3/4			
40-40			



(* CONCEALED JAMBLINER ONLY)

OTHER GRILLE PATTERNS



PRAIRIE PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 32" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	3-4 3/4	6-6 1/8	9-7 1/2
					3-2 1/8	6-3 1/2	9-4 7/8
					3-2 1/8	6-3 1/2	9-4 7/8
					3-1 3/8	6-2 3/4	9-4 1/8
					32	32	32
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	3214	3214-2	3214-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	3216	3216-2	3216-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	3220	3220-2	3220-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	3222	3222-2	3222-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	3224	3224-2	3224-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	3226	3226-2	3226-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	3228	3228-2	3228-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	3230	3230-2	3230-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	3232	3232-2	3232-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	3234	3234-2	3234-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	3236	3236-2	3236-3

1/21/14

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 32" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	3-4 3/4	6-6 1/8	9-7 1/2
Mas. Opg. Clad	3-2 1/8	6-3 1/2	9-4 7/8
Rough Opg.	3-2 1/8	6-3 1/2	9-4 7/8
Frame	3-1 3/8	6-2 3/4	9-4 1/8
Glass	32	32	32

7-2 13/16 / 7-1 1/4 / 7-1 1/4 / 7-0 3/4 / 38-38



3238*



3238-2*



3238-3*

(* CONCEALED JAMBLINER ONLY)


7-6 13/16 / 7-5 1/4 / 7-5 1/4 / 7-4 3/4 / 40-40



3240*


3240-2*


3240-3*

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 36" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	3-8 3/4	7-2 1/8	10-7 1/2
					3-6 1/8	6-11 1/2	10-4 7/8
					3-6 1/8	6-11 1/2	10-4 7/8
					3-5 3/8	6-10 3/4	10-4 1/8
					36	36	36
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	3614	3614-2	3614-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	3616	3616-2	3616-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	3620	3620-2	3620-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	3622	3622-2	3622-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	3624	3624-2	3624-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	3626	3626-2	3626-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	3628	3628-2	3628-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	3630	3630-2	3630-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	3632	3632-2	3632-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	3634	3634-2	3634-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	3636	3636-2	3636-3

1/21/14

OTHER GRILLE PATTERNS



PRAIRIE PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*


* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 36" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"



(* CONCEALED JAMBLINER ONLY)

OTHER GRILLE PATTERNS



UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 40" WIDE

ELEVATIONS
SCALE: 1/8" = 1'-0"


Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	4-0 3/4	7-10 1/8	11-7 1/2
					3-10 1/8	7-7 1/2	11-4 7/8
					3-10 1/8	7-7 1/2	11-4 7/8
					3-9 3/8	7-6 3/4	11-4 1/8
					40	40	40
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	4014	4014-2	4014-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	4016	4016-2	4016-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	4020	4020-2	4020-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	4022	4022-2	4022-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	4024	4024-2	4024-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	4026	4026-2	4026-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	4028	4028-2	4028-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	4030	4030-2	4030-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	4032	4032-2	4032-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	4034	4034-2	4034-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	4036	4036-2	4036-3

1/21/14

OTHER GRILLE PATTERNS



PRAIRIE



PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL


NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.

Pinnacle Series
DOUBLE HUNG - 40" WIDE


ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	4-0 3/4	7-10 1/8
Mas. Opg. Clad	3-10 1/8	7-7 1/2
Rough Opg.	3-10 1/8	7-7 1/2
Frame	3-9 3/8	7-6 3/4
Glass	40	40



(* CLAD CONCEALED JAMBLINER ONLY)

OTHER GRILLE PATTERNS



PRAIRIE PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.


Pinnacle Series
DOUBLE HUNG - 42" WIDE


ELEVATIONS: (CLAD CONCEALED JAMBLINER ONLY)
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed			4-2 3/4	8-2 1/8	12-1 1/2	
Mas. Opg. Clad			4-0 1/8	7-11 1/2	11-10 7/8	
Rough Opg.			4-0 1/8	7-11 1/2	11-10 7/8	
Frame			3-11 3/8	7-10 3/4	11-10 1/8	
Glass			42	42	42	
3-2 13/16	3-1 1/4	3-1 1/4	3-0 3/4	14-14	4214	4214-2	4214-3
3-6 13/16	3-5 1/4	3-5 1/4	3-4 3/4	16-16	4216	4216-2	4216-3
4-2 13/16	4-1 1/4	4-1 1/4	4-0 3/4	20-20	4220	4220-2	4220-3
4-6 13/16	4-5 1/4	4-5 1/4	4-4 3/4	22-22	4222	4222-2	4222-3
4-10 13/16	4-9 1/4	4-9 1/4	4-8 3/4	24-24	4224	4224-2	4224-3
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	26-26	4226	4226-2	4226-3
5-6 13/16	5-5 1/4	5-5 1/4	5-4 3/4	28-28	4228	4228-2	4228-3
5-10 13/16	5-9 1/4	5-9 1/4	5-8 3/4	30-30	4230	4230-2	4230-3
6-2 13/16	6-1 1/4	6-1 1/4	6-0 3/4	32-32	4232	4232-2	4232-3
6-6 13/16	6-5 1/4	6-5 1/4	6-4 3/4	34-34	4234	4234-2	4234-3
6-10 13/16	6-9 1/4	6-9 1/4	6-8 3/4	36-36	4236	4236-2	4236-3

1/21/14

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*


* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.

Pinnacle Series
DOUBLE HUNG - 42" WIDE

ELEVATIONS: (CLAD CONCEALED JAMBLINER ONLY)
SCALE: 1/8" = 1'-0"



OTHER GRILLE PATTERNS



UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*




* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL




NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING




NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.




Pinnacle Series
DOUBLE HUNG - ORIEL




ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	2-0 3/4	3-10 1/8	5-7 1/2
Mas. Opg. Clad	1-10 1/8	3-7 1/2	5-4 7/8
Rough Opg.	1-10 1/8	3-7 1/2	5-4 7/8
Frame	1-9 3/8	3-6 3/4	5-4 1/8
Glass	16	16	16
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
24-36			
	16/3624	16/3624-2	16/3624-3


Mas. Opg. Primed	2-4 3/4	4-6 1/8	6-7 1/2
Mas. Opg. Clad	2-2 1/8	4-3 1/2	6-4 7/8
Rough Opg.	2-2 1/8	4-3 1/2	6-4 7/8
Frame	2-1 3/8	4-2 3/4	6-4 1/8
Glass	20	20	20
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
24-36			
	20/3624	20/3624-2	20/3624-3


Mas. Opg. Primed	2-8 3/4	5-2 1/8	7-7 1/2
Mas. Opg. Clad	2-6 1/8	4-11 1/2	7-4 7/8
Rough Opg.	2-6 1/8	4-11 1/2	7-4 7/8
Frame	2-5 3/8	4-10 3/4	7-4 1/8
Glass	24	24	24
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
24-36			
	24/3624	24/3624-2	24/3624-3

Mas. Opg. Primed	2-10 3/4	5-6 1/8	8-1 1/2
Mas. Opg. Clad	2-8 1/8	5-3 1/2	7-10 7/8
Rough Opg.	2-8 1/8	5-3 1/2	7-10 7/8
Frame	2-7 3/8	5-2 3/4	7-10 1/8
Glass	26	26	26
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
24-36			
	26/3624	26/3624-2	26/3624-3

Mas. Opg. Primed	3-0 3/4	5-10 1/8	8-7 1/2
Mas. Opg. Clad	2-10 1/8	5-7 1/2	8-4 7/8
Rough Opg.	2-10 1/8	5-7 1/2	8-4 7/8
Frame	2-9 3/8	5-6 3/4	8-4 1/8
Glass	28	28	28
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
24-36			
	28/3624	28/3624-2	28/3624-3

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.

1/21/14

Pinnacle Series
DOUBLE HUNG - ORIEL


ELEVATIONS
SCALE: 1/8" = 1'-0"

	30/3624	30/3624-2	30/3624-3
Mas. Opg. Primed	3-2 3/4	6-2 1/8	9-1 1/2
Mas. Opg. Clad	3-0 1/8	5-11 1/2	8-10 7/8
Rough Opg.	3-0 1/8	5-11 1/2	8-10 7/8
Frame	2-11 3/8	5-10 3/4	8-10 1/8
Glass	30	30	30




5-10 13/16 | 5-9 1/4 | 5-9 1/4 | 5-8 3/4 | 24-36

	32/3624	32/3624-2	32/3624-3
Mas. Opg. Primed	3-4 3/4	6-6 1/8	9-7 1/2
Mas. Opg. Clad	3-2 1/8	6-3 1/2	9-4 7/8
Rough Opg.	3-2 1/8	6-3 1/2	9-4 7/8
Frame	3-1 3/8	6-2 3/4	9-4 1/8
Glass	32	32	32




5-10 13/16 | 5-9 1/4 | 5-9 1/4 | 5-8 3/4 | 24-36

	36/3624	36/3624-2	36/3624-3
Mas. Opg. Primed	3-9 3/4	7-2 1/8	10-7 1/2
Mas. Opg. Clad	3-6 1/8	6-11 1/2	10-4 7/8
Rough Opg.	3-6 1/8	6-11 1/2	10-4 7/8
Frame	3-5 3/8	6-10 3/4	10-4 1/8
Glass	36	36	36




5-10 13/16 | 5-9 1/4 | 5-9 1/4 | 5-8 3/4 | 24-36

	40/3624	40/3624-2	40/3624-3
Mas. Opg. Primed	4-0 3/4	7-10 1/8	11-7 1/2
Mas. Opg. Clad	3-10 1/8	7-7 1/2	11-4 7/8
Rough Opg.	3-10 1/8	7-7 1/2	11-4 7/8
Frame	3-9 3/8	7-6 3/4	11-4 1/8
Glass	40	40	40



5-10 13/16 | 5-9 1/4 | 5-9 1/4 | 5-8 3/4 | 24-36

OTHER GRILLE PATTERNS



PRAIRIE PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*




* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL




NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING




NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.




Pinnacle Series
DOUBLE HUNG - COTTAGE




ELEVATIONS
SCALE: 1/8" = 1'-0"

	16/2436	16/2436-2	16/2436-3
Mas. Opg. Primed	2-0 3/4	3-10 1/8	5-7 1/2
Mas. Opg. Clad	1-10 1/8	3-7 1/2	5-4 7/8
Rough Opg.	1-10 1/8	3-7 1/2	5-4 7/8
Frame	1-9 3/8	3-6 3/4	5-4 1/8
Glass	16	16	16
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			


	20/2436	20/2436-2	20/2436-3
Mas. Opg. Primed	2-4 3/4	4-6 1/8	6-7 1/2
Mas. Opg. Clad	2-2 1/8	4-3 1/2	6-4 7/8
Rough Opg.	2-2 1/8	4-3 1/2	6-4 7/8
Frame	2-1 3/8	4-2 3/4	6-4 1/8
Glass	20	20	20
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			


	24/2436	24/2436-2	24/2436-3
Mas. Opg. Primed	2-8 3/4	5-2 1/8	7-7 1/2
Mas. Opg. Clad	2-6 1/8	4-11 1/2	7-4 7/8
Rough Opg.	2-6 1/8	4-11 1/2	7-4 7/8
Frame	2-5 3/8	4-10 3/4	7-4 1/8
Glass	24	24	24
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			

	26/2436	26/2436-2	26/2436-3
Mas. Opg. Primed	2-10 3/4	5-6 1/8	8-1 1/2
Mas. Opg. Clad	2-8 1/8	5-3 1/2	7-10 7/8
Rough Opg.	2-8 1/8	5-3 1/2	7-10 7/8
Frame	2-7 3/8	5-2 3/4	7-10 1/8
Glass	26	26	26
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			

	28/2436	28/2436-2	28/2436-3
Mas. Opg. Primed	3-0 3/4	5-10 1/8	8-7 1/2
Mas. Opg. Clad	2-10 1/8	5-7 1/2	8-4 7/8
Rough Opg.	2-10 1/8	5-7 1/2	8-4 7/8
Frame	2-9 3/8	5-6 3/4	8-4 1/8
Glass	28	28	28
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*




* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL




NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING




NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.




Pinnacle Series
DOUBLE HUNG - COTTAGE

ELEVATIONS
SCALE: 1/8" = 1'-0"


	30/3624	30/3624-2	30/3624-3
Mas. Opg. Primed	3-2 3/4	6-2 1/8	9-1 1/2
Mas. Opg. Clad	3-0 1/8	5-11 1/2	8-10 7/8
Rough Opg.	3-0 1/8	5-11 1/2	8-10 7/8
Frame	2-11 3/8	5-10 3/4	8-10 1/8
Glass	30	30	30
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			


	32/3624	32/3624-2	32/3624-3
Mas. Opg. Primed	3-4 3/4	6-6 1/8	9-7 1/2
Mas. Opg. Clad	3-2 1/8	6-3 1/2	9-4 7/8
Rough Opg.	3-2 1/8	6-3 1/2	9-4 7/8
Frame	3-1 3/8	6-2 3/4	9-4 1/8
Glass	32	32	32
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			

	36/2436	36/2436-2	36/2436-3
Mas. Opg. Primed	3-9 3/4	7-2 1/8	10-7 1/2
Mas. Opg. Clad	3-6 1/8	6-11 1/2	10-4 7/8
Rough Opg.	3-6 1/8	6-11 1/2	10-4 7/8
Frame	3-5 3/8	6-10 3/4	10-4 1/8
Glass	36	36	36
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			

	40/2436	40/2436-2	40/2436-3
Mas. Opg. Primed	4-0 3/4	7-10 1/8	11-7 1/2
Mas. Opg. Clad	3-10 1/8	7-7 1/2	11-4 7/8
Rough Opg.	3-10 1/8	7-7 1/2	11-4 7/8
Frame	3-9 3/8	7-6 3/4	11-4 1/8
Glass	40	40	40
5-10 13/16			
5-9 1/4			
5-9 1/4			
5-8 3/4			
36-24			

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*


* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.

Pinnacle Series
DOUBLE HUNG - PICTURE

ELEVATIONS
SCALE: 1/8" = 1'-0"



UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*


FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

OTHER GRILLE PATTERNS



PRAIRIE PLAZA

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MAS. OPENING.
*ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 3/32" FOR BELLY SILL

1/21/14

Pinnacle Series
DOUBLE HUNG - TRANSOM

ELEVATIONS
SCALE: 1/8" = 1'-0"

CLAD (IN SASH)

Mas. Opg. Clad	Rough Opg.	Frame	Glass	1-10 1/8	2-2 1/8	2-6 1/8	2-8 1/8	2-10 1/8	3-01/8	3-2 1/8	3-6 1/8	3-10 1/8	4-0 1/8	4-2 1/8	5-2 1/8
				1-10 1/8	2-2 1/8	2-6 1/8	2-8 1/8	2-10 1/8	3-0 1/8	3-2 1/8	3-6 1/8	3-10 1/8	4-0 1/8	4-2 1/8	5-2 1/8
				1-9 3/8	2-1 3/8	2-5 3/8	2-7 3/8	2-9 3/8	2-11 3/8	3-1 3/8	3-5 3/8	3-9 3/8	3-11 3/8	4-1 3/8	5-1 3/8
				17 3/8	21 3/8	25 3/8	27 3/8	29 3/8	31 3/8	33 3/8	37 3/8	41 3/8	43 3/8	45 3/8	57 3/8
1-0 1/2	1-0 1/2	1-0	8	1608	2008	2408	2608	2808	3008	3208	3608	4008	4208	4408	5608
1-2 1/2	1-2 1/2	1-2	10	1610	2010	2410	2610	2810	3010	3210	3610	4010	4210	4410	5610
1-4 1/2	1-4 1/2	1-4	12	1612	2012	2412	2612	2812	3012	3212	3612	4012	4212	4412	5612
1-6 1/2	1-6 1/2	1-6	14	1614	2014	2414	2614	2814	3014	3214	3614	4014	4214	4414	5614
2-0 1/2	2-0 1/2	2-0	20	1620	2020	2420	2620	2820	3020	3220	3620	4020	4220	4420	5620
2-6 1/2	2-6 1/2	2-6	26	1626	2026	2426	2626	2826	3026	3226	3626	4026	4226	4426	5626
3-0 1/2	3-0 1/2	3-0	32	1632	2032	2432	2632	2832	3032	3232	3632	4032	4232	4432	5632

PRIMED (IN SASH)

Mas. Opg. Primed	Rough Opg.	Frame	Glass	2-0 3/4	2-4 3/4	2-8 3/4	2-10 3/4	3-0 3/4	3-2 3/4	3-4 3/4	3-8 3/4	4-0 3/4	4-4 3/4	5-4 3/4	6-4 3/4
				1-10 1/8	2-2 1/8	2-6 1/8	2-8 1/8	2-10 1/8	3-0 1/8	3-2 1/8	3-6 1/8	3-10 1/8	4-2 1/8	5-2 1/8	6-2 1/8
				1-9 3/8	2-1 3/8	2-5 3/8	2-7 3/8	2-9 3/8	2-11 3/8	3-1 3/8	3-5 3/8	3-9 3/8	4-1 3/8	5-1 3/8	6-1 3/8
				16	20	24	26	28	30	32	36	40	44	56	68
1-4 5/8	1-2 1/16	1-1 9/16	8	1608	2008	2408	2608	2808	3008	3208	3608	4008	4408	5608	6808
1-6 5/8	1-4 1/16	1-3 9/16	10	1610	2010	2410	2610	2810	3010	3210	3610	4010	4410	5610	6810
1-8 5/8	1-6 1/16	1-5 9/16	12	1612	2012	2412	2612	2812	3012	3212	3612	4012	4412	5612	6812
1-10 5/8	1-8 1/16	1-7 9/16	14	1614	2014	2414	2614	2814	3014	3214	3614	4014	4414	5614	6814
2-4 5/8	2-2 1/16	2-1 9/16	20	1620	2020	2420	2620	2820	3020	3220	3620	4020	4420	5620	6820
2-10 5/8	2-8 1/16	2-7 9/16	26	1626	2026	2426	2626	2826	3026	3226	3626	4026	4426	5626	6826
3-4 5/8	3-2 1/16	3-1 9/16	32	1632	2032	2432	2632	2832	3032	3232	3632	4032	4432	5632	6832

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MAS. OPENING.
*ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 3/32" FOR BELLY SILL

OTHER GRILLE PATTERNS


PRAIRIE


PLAZA


1/21/14

Pinnacle Series
SINGLE HUNG - ORIEL


ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	2-0 3/4	2-4 3/4	2-8 3/4	3-0 3/4	3-4 3/4
Mas. Opg. Clad	1-10 1/8	2-2 1/8	2-6 1/8	2-10 1/8	3-2 1/8
Rough Opg.	1-10 1/8	2-2 1/8	2-6 1/8	2-10 1/8	3-2 1/8
Frame	1-9 3/8	2-1 3/8	2-5 3/8	2-9 3/8	3-1 3/8
Glass	16	20	24	28	32
7-1 9/16					
7-0					
7-0					
6-11 1/2					
28-46 3/4					
	16/4628	20/4628	24/4628	28/4628	32/4628
7-7 9/16					
7-6					
7-6					
7-5 1/2					
28-52 3/4					
	16/5228	20/5228	24/5228	28/5228	32/5228
8-1 9/16					
8-0					
8-0					
7-11 1/2					
28-58 3/4					
	16/5828	20/5828	24/5828	28/5828	32/5828

OTHER GRILLE PATTERNS



PRAIRIE



PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.

Pinnacle Series
SINGLE HUNG - SEGMENT TOP

ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed		2-8 3/4		3-0 3/4		3-4 3/4	
Mas. Opg. Clad		2-6 1/8		2-10 1/8		3-2 1/8	
Rough Opg.		2-6 1/8		2-10 1/8		3-2 1/8	
Frame		2-5 3/8		2-9 3/8		3-1 3/8	
Glass		24		28		32	
4-10 5/8	4-9 1/16	4-9 1/16	4-8 9/16	22-26	2422	2822	3222
5-2 5/8	5-1 1/16	5-1 1/16	5-0 9/16	24-28	2424	2824	3224
5-6 5/8	5-5 1/16	5-5 1/16	5-4 9/16	26-30	2426	2826	3226
5-10 5/8	5-9 1/16	5-9 1/16	5-8 9/16	28-32	2428	2828	3228
6-2 5/8	6-1 1/16	6-1 1/16	6-0 9/16	30-34	2430	2830	3230
6-6 5/8	6-5 1/16	6-5 1/16	6-4 9/16	32-36	2432	2832	3232
6-10 5/8	6-9 1/16	6-9 1/16	6-8 9/16	34-38	2434	2834	3234
7-2 5/8	7-1 1/16	7-1 1/16	7-0 9/16	36-40	2436	2836	3236

1/21/14

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.

Pinnacle Series
SINGLE HUNG - ROUND TOP

ELEVATIONS
SCALE: 1/8" = 1'-0"

Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	2-8 3/4	3-0 3/4	3-4 3/4
					2-6 1/8	2-10 1/8	3-2 1/8
					2-6 1/8	2-10 1/8	3-2 1/8
					2-5 3/8	2-9 3/8	3-1 3/8
					24	28	32
5-6 15/16	5-5 3/8	5-5 3/8	5-4 7/8	22	2422	2822	3222
5-10 15/16	5-9 3/8	5-9 3/8	5-8 7/8	24	2424	2824	3224
6-2 15/16	6-1 3/8	6-1 3/8	6-0 7/8	26	2426	2826	3226
6-6 15/16	6-5 3/8	6-5 3/8	6-4 7/8	28	2428	2828	3228
6-10 15/16	6-9 3/8	6-9 3/8	6-8 7/8	30	2430	2830	3230
7-2 15/16	7-1 3/8	7-1 3/8	7-0 7/8	32	2432	2832	3232
7-6 15/16	7-5 3/8	7-5 3/8	7-4 7/8	34	2434	2834	3234
7-10 15/16	7-9 3/8	7-9 3/8	7-8 7/8	36	2436	2836	3236

5-8 15/16	5-7 3/8	5-7 3/8	5-6 7/8	22			
6-0 15/16	5-11 3/8	5-11 3/8	5-10 7/8	24			
6-4 15/16	6-3 3/8	6-3 3/8	6-2 7/8	26			
6-8 15/16	6-7 3/8	6-7 3/8	6-6 7/8	28			
7-0 15/16	6-11 3/8	6-11 3/8	6-10 7/8	30			
7-4 15/16	7-3 3/8	7-3 3/8	7-2 7/8	32			
7-8 15/16	7-7 3/8	7-7 3/8	7-6 7/8	34			
8-0 15/16	7-11 3/8	7-11 3/8	7-10 7/8	36			

5-10 15/16	5-9 3/8	5-9 3/8	5-8 7/8	22			
6-2 15/16	6-1 3/8	6-1 3/8	6-0 7/8	24			
6-6 15/16	6-5 3/8	6-5 3/8	6-4 7/8	26			
6-10 15/16	6-9 3/8	6-9 3/8	6-8 7/8	28			
7-2 15/16	7-1 3/8	7-1 3/8	7-0 7/8	30			
7-6 15/16	7-5 3/8	7-5 3/8	7-4 7/8	32			
7-10 15/16	7-9 3/8	7-9 3/8	7-8 7/8	34			
8-2 15/16	8-1 3/8	8-1 3/8	8-0 7/8	36			

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180
- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING
- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND
- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING
- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG
- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION
- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 15/16" FOR BULLNOSE SILL
ADD ADDITIONAL 1 1/32" FOR BELLY SILL
CASING OPTIONS MAY BE LIMITED BY SIZE DUE TO MINIMUM RADIUS RESTRICTIONS.

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS VERIFY LOCAL CODES.