

Pinnacle Series

CLAD GLIDE-BY

MEASUREMENT CONVERSIONS

STANDARD (NO CASING)													
Size Referenced	Daylite Opening		Glass Size		Frame Size		Rough Opening		Unit Size		Masonry Opening		
Dimension Given	Daylite Opening	Dimension Needed											
				Width	+ 1	Width	x2 + 8 3/16	Width	x2 + 8 5/16	Width	x2 + 8 3/16	Width	x2 + 8 5/16
			Height	+ 1	Height	+ 7 3/4	Height	+ 8 1/4	Height	+ 7 3/4	Height	+ 8 1/4	
	Glass Size	Width	- 1			Width	x2 + 7 3/16	Width	x2 + 7 15/16	Width	x2 + 7 3/16	Width	x2 + 7 15/16
		Height	- 1			Height	+ 6 3/4	Height	+ 7 1/4	Height	+ 6 3/4	Height	+ 7 1/4
	Frame Size	Width	(- 8 3/16) / 2	Width	(- 7 3/16) / 2			Width	+ 3/4	Width	+ 0	Width	+ 3/4
		Height	- 7 3/4	Height	- 6 3/4			Height	+ 1/2	Height	+ 0	Height	+ 3/4
	Rough Opening	Width	(- 8 5/16) / 2	Width	(- 7 15/16) / 2	Width	- 3/4			Width	- 3/4	Width	+ 0
		Height	- 8 1/4	Height	- 7 1/4	Height	- 1/2			Height	- 1/2	Height	+ 0
	Unit Size	Width	(- 8 3/16) / 2	Width	(- 7 3/16) / 2	Width	+ 0	Width	+ 3/4			Width	+ 3/4
		Height	- 7 3/4	Height	- 6 3/4	Height	+ 0	Height	+ 1/2			Height	+ 1/2
	Masonry Opening	Width	(- 8 5/16) / 2	Width	(- 7 15/16) / 2	Width	- 3/4	Width	+ 0	Width	- 3/4		
Height		- 8 1/4	Height	- 7 1/4	Height	- 1/2	Height	+ 0	Height	- 3/4			

FRAME TO UNIT CASING ADDERS

WM180 Brickmould	3/8" Subsill	+ 2 13/16	Width
		+ 1 3/4	Height
	1 1/4" Subsill	+ 2 13/16	Width
		+ 2 11/16	Height
	2 1/4" Subsill	2 13/16	Width
		+ 3 11/16	Height
Williamsburg Casing	3/8" Subsill	+ 6 1/2	Width
		+ 3 5/8	Height
	1 1/4" Subsill	+ 6 1/2	Width
		+ 4 1/2	Height
	2 1/4" Subsill	+ 6 1/2	Width
		+ 5 1/2	Height
3 1/2" Flat Casing	3/8" Subsill	+ 5 7/8	Width
		+ 3 5/16	Height
	1 1/4" Subsill	+ 5 7/8	Width
		+ 4 3/16	Height
	2 1/4" Subsill	+ 5 7/8	Width
		+ 5 3/16	Height