

# Pinnacle Select Series

## CLAD AWNING

### DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

| Operating     |                  |                   |        |                   |                            |
|---------------|------------------|-------------------|--------|-------------------|----------------------------|
| Series        | Window Type      | Performance Level | Size   | Performance Grade | Air Infiltration (cfm/ft2) |
| Pinnacle Clad | Awning Crank-Out | Standard          | 6060-1 | LC-PG50-AP        | 0.02                       |

**Notes:**

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

| Minimum and Maximum Measurements |                      |                     |                      |
|----------------------------------|----------------------|---------------------|----------------------|
| Minimum Frame Width              | Minimum Frame Height | Maximum Frame Width | Maximum Frame Height |
| Operating                        |                      |                     |                      |
| 1-8                              | 1-6                  | 5-0                 | 4-0                  |
| Stationary / Picture / Transom   |                      |                     |                      |
| 1-6                              | 1-0                  | 6-0                 | 6-6                  |