

# Next Dimension Signature Series

## RADIUS

### DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Standard					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Signature Vinyl	Radius	Standard	9672	LC-PG40-FW	0.10
ND Signature Vinyl	Radius	Standard	8482	LC-PG45-FW	0.10
ND Signature Vinyl	Radius	Standard	7272	LC-PG50-FW	0.10

**Notes:**

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
<b>Half Round</b>			
2-0	1-0	8-0	3-11 3/4
<b>Quarter Round</b>			
2-0	2-0	4-0	4-0
<b>Special Shapes</b>			
2-0	1-0	8-0*	8-0*
<b>Eyebrow</b>			
2-6	1-2		
<b>Ellipse</b>			
4-0	1-5		
<b>Oval</b>			
2-0	3-0		

\*Maximum sq.ft. 4'-0", Aspect ratio 7 to 1

Radius Misc.: Minimum radius 9" & minimum leg height