

Pinnacle Series


CLAD AWNING

ELEVATIONS : OPERATING / STATIONARY

SCALE: 1/8" = 1'-0"

Rough Opp. Frame Glass		2-0 3/4	2-4 3/4	2-6 3/4	3-0 3/4	3-6 3/4	4-0 3/4	4-6 3/4	5-0 3/4
		2-0 20	2-4 24	2-6 26	3-0 32	3-6 38	4-0 44	4-6 50	5-0 56
1-6 1/2	1-6 14	 2014	 2414	 2614	 3214	 3814	 4414	 5014	 5614
1-8 1/2	1-8 16	 2016	 2416	 2616	 3216	 3816	 4416	 5016	 5616
2-0 1/2	2-0 20	 2020	 2420	 2620	 3220	 3820	 4420	 5020	 5620
2-4 1/2	2-4 24	 2024	 2424	 2624	 3224	 3824	 4424	 5024	 5624
2-6 1/2	2-6 26	 2026	 2426	 2626	 3226	 3826	 4426	 5026	 5626
3-0 1/2	3-0 32	 2032	 2432	 2632	 3232	 3832	 4432	 5032	 5632
3-6 1/2	3-6 38	 2038	 2438	 2638	 3238	 3838	 4438	 5038	 5638
4-0 1/2	4-0 44	 2044	 2444	 2644	 3244	 3844	 4444	 5044	 5644
4-6 1/2	4-6 50	 2050	 2450	 2650	 3250	 3850	 4450	 5050	 5650
5-0 1/2	5-0 56	 2056	 2456	 2656	 3256	 3856	 4456	 5056	 5656

OPERATION




OPERATING



STATIONARY

OTHER GRILLE PATTERN



PRAIRIE

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOULD