

Next Dimension Pro Series

SINGLE HUNG - STANDARD FRAME

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Single Hung					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Pro Std Vinyl	Single-Hung	Standard	2460	R-PG35-H	0.19
ND Pro Std Vinyl	Single-Hung	Standard	3678	R-PG30-H	0.13
ND Pro Std Vinyl	Single-Hung	Standard	3618-3660	R-PG30-H	0.11
ND Pro Std Vinyl	Single-Hung	Standard	3024-3048	R-PG35-H	0.12
ND Pro Std Vinyl	Single-Hung	Standard	9024-3048	R-PG30-H	0.14
ND Pro Std Vinyl	Single-Hung	Standard	3660	LC-PG40-H	0.08
ND Pro Std Vinyl	Single-Hung	Standard	2424-2448	LC-PG35-H	0.16
ND Pro Std Vinyl	Single-Hung	Standard	4278	R-PG30-H	0.17
ND Pro Std Vinyl	Single-Hung	Standard	4218-4254	R-PG30-H	0.09
ND Pro Std Vinyl	Single-Hung	Standard	4884	R-PG30-H	0.10
ND Pro Std Vinyl	Single-Hung	Standard	4578	LC-PG35-H	0.11
ND Pro Std Vinyl	Single-Hung	DP Upgrade	4278	R-PG40-H	0.09

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
Operating			
1-0	2-0	4-0	7-0

Next Dimension Pro Series

SINGLE HUNG - BRICKMOULD FRAME

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Single Hung					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Pro BM Vinyl	Single-Hung	Standard	3678-3 1-lock	LC-PG30-H	0.13
ND Pro BM Vinyl	Single-Hung	Standard	9024-1/3048-3	R-PG30-H	0.16
ND Pro BM Vinyl	Single-Hung	Standard	3618-3/3660-3	R-PG35-H	0.09
ND Pro BM Vinyl	Single-Hung	Standard	4278-2 2-lock	R-PG30-H	0.12
ND Pro BM Vinyl	Single-Hung	Standard	4884-1 2-lock	LC-PG35-H	0.10
ND Pro BM Vinyl	Single-Hung	Standard	4578-1 2-lock	LC-PG40-H	0.10

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
Operating			
1-0	2-0	4-0	7-0