

Next Dimension Signature Series

CASEMENT

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Casement					
Series	Window Type	Performance Level	Rough Opening	Performance Grade	Air Infiltration (cfm/ft2)
ND Signature Vinyl	Casement Crank-Out	Standard	3672	R-PG50-C	0.07

Fixed Casement (Stationary, Picture, Transom)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Signature Vinyl	Casement Fixed	Standard	3672	R-PG50-FW	0.01

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
Operating			
1-4	1-6	3-0*	6-0**
Stationary / Picture / Transom			
1-0	1-0	8-0***	8-0***

*Up to 5'-0" frame height

**Up to 2'-6" frame width

***Not exceed 7'-0" in both directions