

Next Dimension Signature Series

SINGLE HUNG

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Single Hung					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Signature Vinyl	Single-Hung	Standard	4878	R-PG25-H	0.09
ND Signature Vinyl	Single-Hung	Standard	3660	R-PG35-H	0.18
Fixed Single Hung (Stationary, Picture, Transom)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Signature Vinyl	Single-Hung Picture	Standard	4477	LC-PG30-FW	0.10
ND Signature Vinyl	Single-Hung Picture	Standard	7272	LC-PG40-FW	0.10

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
Operating			
1-6	2-0	4-0	7-0