

Legend Series

DIRECT SET

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Direct Glazed					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Legend CPVC	Direct Set In-Sash	Standard	10869	LC-PG50-TR	0.11
Legend CPVC	Direct Set In-Sash	Standard	8484	LC-PG25-TR	0.10
Legend CPVC	Direct Set In-Sash	Standard	7450	R-PG40-TR	0.01
Legend CPVC	Direct Set In-Sash	Standard	6832	LC-PG50-TR	0.11
Legend CPVC	Direct Glaze In-Sash	Standard	10856	LC-PG65-FW	0.01
Legend CPVC	Direct Glaze In-Sash	Standard	10884	LC-PG50	0.1

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Standard			
1-2*	1-2*	11-11*	11-11*

*5 1/2" pitch or 22 degrees

**Frame dimension can not exceed 85" in both directions; Aspect ratio 7 to 1