

Legend Series


AWNING

ELEVATIONS : OPERATING / STATIONARY

SCALE: 1/8" = 1'-0"

	Masonry Opg. Rough Opg. Frame Glass		2-3 9/16	2-7 9/16	2-9 9/16	3-3 9/16	3-9 9/16	4-3 9/16	
			2-0 3/4	2-4 3/4	2-6 3/4	3-0 3/4	3-6 3/4	4-0 3/4	
			2-0	2-4	2-6	3-0	3-6	4-0	
			20	24	26	32	38	44	
1-8 15/16	1-7 1/4	1-6	14						
				2014	2414	2614	3214	3814	4414
1-10 15/16	1-9 1/4	1-8	16						
				2016	2416	2616	3216	3816	4416
2-2 15/16	2-1 1/4	2-0	20						
				2020	2420	2620	3220	3820	4420
2-6 15/16	2-5 1/4	2-4	24						
				2024	2424	2624	3224	3824	4424
2-8 15/16	2-7 1/4	2-6	26						
				2026	2426	2626	3226	3826	4426
3-2 15/16	3-1 1/4	3-0	32						
						3232	3832	4432	

OPERATION




OPERATING



STATIONARY

(AS VIEWED FROM EXTERIOR)

OTHER GRILLE PATTERN



PRAIRIE

UNIT SIZE INFORMATION

180 BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 2 7/16" TO FRAME HEIGHT

3 1/2" FLAT CASING

- ADD 5 13/16" TO FRAME WIDTH
- ADD 3 15/16" TO FRAME HEIGHT

4 1/2" BACKBAND

- ADD 7 13/16" TO FRAME WIDTH
- ADD 4 15/16" TO FRAME HEIGHT

5 1/2" FLAT CASING

- ADD 9 13/16" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT

WILLIAMSBURG

- ADD 5 3/8" TO FRAME WIDTH
- ADD 3 11/16" TO FRAME HEIGHT

PLANTATION

- ADD 5 13/16" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT

* ADD ADDITIONAL 1" FOR BULLNOSE SUBSILL

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:

MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOULD