




NEXT DIMENSION PRO SERIES

4-WAY MULL REINFORCEMENT GUIDELINES

MULLION

NOTE: SIZES SHOWN ARE FOR **INDIVIDUAL UNITS** WITHIN THE MULLED CONFIGURATION

		WINDOW WIDTH [IN]										
		18	24	30	36	42	48	54	60	66	72	78
WINDOW HEIGHT [IN]	18	50	50	50	40	35	30	25	25	20	20	20
	24	50	50	50	40	35	30	25	25	20	20	20
	30	50	50	30	25	20	20					
	36	40	40	20								
	42	35	35	20								
	48	30	30									
	54	25	25									
	60	25	25									
	66	20	20									
	72	20	20									
	78	20	20									



-  No Reinforcement
-  Reinforcement Required
-  Exceeds Mulling Limitations

Numbers shown are calculated **STRUCTURAL DP Rating** for the **mull ONLY**
 Refer to individual unit ratings for structural, air and water performance of the individual unit(s).
 For composite structural rating use the **LOWER** of the mull and unit(s) individual structural ratings.

RULES FOR REINFORCEMENT LOCATION

Unequal number of vertical and horizontal mullions: place the reinforcement in the direction of the largest quantity of mullions.

Equal number of vertical and horizontal mullions: place the reinforcement in the mullion(s) that are shortest in length.



- Notes: 1) Use Largest Width (W) and Height (H)
- 2) Maximum Deflection: Span / 30
- 3) Rebar Specs: 1/4" x 1 7/8" Steel Bar
- 4) Overall Mulling Configuration not to Exceed: 96" x 84"