Pinnacle Series


CLAD AWNING

ELEVATIONS : OPERATING / STATIONARY

SCALE: 1/8" = 1'-0"

Rough Opg.	Frame	Glass	2-0 3/4	2-4 3/4	2-6 3/4	2-8 3/4	3-0 3/4	3-6 3/4	4-0 3/4	4-6 3/4	5-0 3/4
			2-0	2-4	2-6	2-8	3-0	3-6	4-0	4-6	5-0
			20	24	26	28	32	38	44	50	56
1-6 1/2	1-6	14	2014	2414	2614	2814	3214	3814	4414	5014	5614
1-8 1/2	1-8	16	2016	2416	2616	2816	3216	3816	4416	5016	5616
2-0 1/2	2-0	20	2020	2420	2620	2820	3220	3820	4420	5020	5620
2-4 1/2	2-4	24	2024	2424	2624	2824	3224	3824	4424	5024	5624
2-6 1/2	2-6	26	2026	2426	2626	2826	3226	3826	4426	5026	5626
3-0 1/2	3-0	32	2032	2432	2632	2832	3232	3832	4432	5032	5632
3-6 1/2	3-6	38	2038	2438	2638	2838	3238	3838	4438	5038	5638
4-0 1/2	4-0	44	2044	2444	2644	2844	3244	3844	4444	5044	5644
4-6 1/2	4-6	50	2050	2450	2650	2850	3250	3850	4450	5050	5650
5-0 1/2	5-0	56	2056	2456	2656	2856	3256	3856	4456	5056	5656

OPERATION



OPERATING STATIONARY

OTHER GRILLE PATTERN



PRAIRIE

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD
- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG
- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOULD