

Next Dimension Classic Series

SINGLE HUNG

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Single Hung					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Classic Vinyl	Single-Hung	Standard	3684-3	LC-PG35-H	0.17
ND Classic Vinyl	Single-Hung	Standard	4884-2	LC-PG35-H	0.19
ND Classic Vinyl	Single-Hung	Standard	3661-2	LC-PG45-H	0.13
ND Classic Vinyl	Single-Hung	Standard	3661-1	LC-PG50-H	0.27
ND Classic Vinyl	Single-Hung	Standard	4884-1	LC-PG40-H	0.18
ND Classic Vinyl	Single-Hung	Standard	4564-1	R-PG35-H	0.2
ND Classic Vinyl	Single-Hung	Standard	3672-1	R-PG50-H	0.1

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
Operating			
1-6	2-6	4-0	7-0