

Pinnacle Impact Series

CLAD DOUBLE HUNG

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Double Hung					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Pinnacle Clad	Double-Hung	Impact	3234	LC-PG50-H	0.27

Fixed Double Hung (Stationary, Picture, Transom)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Pinnacle Clad	Double-Hung Picture	Impact	4470	LC-PG50-FW	0.12

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Operating			
1-9 3/8	2-8 3/4	3-9 3/8	6-8 3/4
Picture			
1-1 3/8	2-10 3/4	6-1 3/8	6-4 3/4
Transom			
1-9 3/8	1-0	6-1 3/8	3-0