

Pinnacle Series

GLIDE-BY

ELEVATIONS

SCALE: 1/8" = 1'-0"

	Mas. Opg. Primed	Mas. Opg. Clad	Rough Opg.	Frame	Glass	3-6 9/16	4-2 9/16	4-10 9/16	5-2 9/16	5-6 9/16	6-2 9/16
						3-3 15/16	3-11 15/16	4-7 15/16	4-11 15/16	5-3 15/16	5-11 15/16
						3-3 15/16	3-11 15/16	4-7 15/16	4-11 15/16	5-3 15/16	5-11 15/16
						3-3 3/16	3-11 3/16	4-7 3/16	4-11 3/16	5-3 3/16	5-11 3/16
						16-16	20-20	24-24	26-26	28-28	32-32
2-0 13/16	2-0 13/16	1-11 1/4	1-11 1/4	1-10 3/4	16						
						1616	2016	2416	2616	2816	3216
2-4 13/16	2-3 1/4	2-3 1/4	2-2 3/4	2-2 3/4	20						
						1620	2020	2420	2620	2820	3220
3-0 13/16	2-11 1/4	2-11 1/4	2-10 3/4	2-10 3/4	28						
						1628	2028	2428	2628	2828	3228
3-4 13/16	3-3 1/4	3-3 1/4	3-2 3/4	3-2 3/4	32						
						1632	2032	2432	2632	2832	3232
3-8 13/16	3-7 1/4	3-7 1/4	3-6 3/4	3-6 3/4	36						
						1636	2036	2436	2636	2836	3236
4-0 13/16	3-11 1/4	3-11 1/4	3-10 3/4	3-10 3/4	40						
						1640	2040	2440	2640	2840	3240
4-8 13/16	4-7 1/4	4-7 1/4	4-6 3/4	4-6 3/4	48						
						1648	2048	2448	2648	2848	3248
5-2 13/16	5-1 1/4	5-1 1/4	5-0 3/4	5-0 3/4	54						
						1654	2054	2454	2654	2854	3254

UNIT SIZE INFORMATION

FOR CLAD BRICKMOLD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180

- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING

- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND

- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING

- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*


FOR PRIMED WILLIAMSBURG

- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*


FOR PRIMED PLANTATION

- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

OTHER GRILLE PATTERNS




PRAIRIE



SINGLE PLAZA



DOUBLE PLAZA




TRIPLE PLAZA




DIAMOND

HANDING



XO



OX

NOTE: ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

*ADD ADDITIONAL 15/16" FOR BULLNOSE SILL

ADD ADDITIONAL 1 1/32" FOR BELLY SILL

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.

PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.

SHADED SIZES MEET MOST EGRESS REQUIREMENTS. VERIFY LOCAL CODES.

Pinnacle Series

GLIDE-BY - TRIPLES

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opg. Primed
Mas. Opg. Clad
Rough Opg.
Frame
Glass

Unit Height	Unit Width	Unit Height	Unit Width	Unit Height	Unit Width	Unit Height	Unit Width
3-0 13/16	6-4 1/16	7-8 1/16	8-0 1/16	9-0 1/16			
1-11 1/4	6-1 7/16	7-5 7/16	7-9 7/16	8-9 7/16			
2-11 1/4	6-1 7/16	7-5 7/16	7-9 7/16	8-9 7/16			
2-10 3/4	6-0 11/16	7-4 11/16	7-8 11/16	8-8 11/16			
28	16-32-16	20-40-20	28-28-28	24-48-24			
4-0 13/16	6-4 1/16	7-8 1/16	8-0 1/16	9-0 1/16			
3-11 1/4	6-1 7/16	7-5 7/16	7-9 7/16	8-9 7/16			
3-11 1/4	6-1 7/16	7-5 7/16	7-9 7/16	8-9 7/16			
3-10 3/4	6-0 11/16	7-4 11/16	7-8 11/16	8-8 11/16			
40	16-32-1640	20-40-2040	28-28-2840	24-48-2440			
4-8 13/16	6-4 1/16	7-8 1/16	8-0 1/16	9-0 1/16			
4-7 1/4	6-1 7/16	7-5 7/16	7-9 7/16	8-9 7/16			
4-7 1/4	6-1 7/16	7-5 7/16	7-9 7/16	8-9 7/16			
4-6 3/4	6-0 11/16	7-4 11/16	7-8 11/16	8-8 11/16			
48	16-32-1648	20-40-2048	28-28-2848	24-48-2448			
5-2 13/16	6-4 1/16	7-8 1/16	8-0 1/16	9-0 1/16			
5-1 1/4	6-1 7/16	7-5 7/16	7-9 7/16	8-9 7/16			
5-1 1/4	6-1 7/16	7-5 7/16	7-9 7/16	8-9 7/16			
5-0 3/4	6-0 11/16	7-4 11/16	7-8 11/16	8-8 11/16			
54	16-32-1654	20-40-2054	28-28-2854	24-48-2454			

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR PRIMED WM-180

- ADD 2 19/32" TO FRAME WIDTH
- ADD 1 9/16" TO FRAME HEIGHT*

FOR PRIMED 3 1/2" FLAT CASING

- ADD 5 5/8" TO FRAME WIDTH
- ADD 3 1/16" TO FRAME HEIGHT*

FOR PRIMED 4 1/2" BACKBAND

- ADD 7 5/8" TO FRAME WIDTH
- ADD 4 1/16" TO FRAME HEIGHT*

FOR PRIMED 5 1/2" FLAT CASING

- ADD 9 5/8" TO FRAME WIDTH
- ADD 5 1/16" TO FRAME HEIGHT*

FOR PRIMED WILLIAMSBURG

- ADD 5 1/8" TO FRAME WIDTH
- ADD 2 13/16" TO FRAME HEIGHT*

FOR PRIMED PLANTATION


- ADD 5 5/8" TO FRAME WIDTH
- ADD 5 15/16" TO FRAME HEIGHT*

NOTE: ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING


*ADD ADDITIONAL 15/16" FOR BULLNOSE SILL

ADD ADDITIONAL 1 1/32" FOR BELLY SILL


OTHER GRILLE PATTERNS




PRAIRIE




DIAMOND



SINGLE PLAZA




DOUBLE PLAZA



TRIPLE PLAZA

HANDING



XOX

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.

PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOLD.

SHADED SIZES MEET MOST EGRESS REQUIREMENTS. VERIFY LOCAL CODES.