

Revive Series

HYBRID DOUBLE HUNG

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Double Hung					
Series	Window Type	Performance Level	R.O. Size	Performance Grade	Air Infiltration (cfm/ft ²)
Revive Clad w/ CPVC Sash	Double-Hung	Standard	41 7/8" x 79 11/16"	LC-PG30-H	.24
Fixed Double Hung (Picture)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft ²)
Revive Clad w/ CPVC Sash	Double-Hung Picture	Standard	61 7/8" 76 25/32"	LC-PG30-F	0.17

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Operating			
1-9 3/8	2-8 3/4	3-9 3/8	8-0 3/4
Picture			
1-1 3/8	2-10 3/4	6-1 3/8	8-0 3/4