




NEXT DIMENSION PRO SERIES

4 - WAY MULL REINFORCEMENT GUIDELINES

Uni-Frame Construction with T-BAR

NOTE: SIZES SHOWN ARE FOR **INDIVIDUAL UNITS** WITHIN THE MULLED CONFIGURATION



		WINDOW WIDTH [IN]										
		18	24	30	36	42	48	54	60	66	72	78
WINDOW HEIGHT [IN]	18	50	50	50	50	50	50	50	50	50	50	50
	24	50	50	50	50	50	50	50	50	50	50	50
	30	50	50	50	50	50	50	50	50	50	50	50
	36	50	50	50	50	50	50	50	45	40	40	
	42	50	50	50	50	50	45	40	35	35	30	30
	48	40	40	40	35	30	25	25	20	20	20	
	54	35	35	25	20	20						
	60	20	20									
	66											
	72											
	78											

-  No Reinforcement
-  Reinforcement Required
-  Exceeds Mulling Limitations

Numbers shown are calculated **STRUCTURAL DP Rating** for the **mull ONLY**.
 Refer to individual unit ratings for structural, air and water performance of the individual unit(s).
 For composite structural rating use the **LOWER** of the mull and unit(s) individual structural ratings.

RULES FOR REINFORCEMENT LOCATION

Reinforcement is placed in the vertical mullions



- Notes:
- 1) Use Largest Width (W) and Height (H)
 - 2) Maximum Deflection: $\text{Span} / 30$
 - 3) Rebar Specs: Aluminum I-Beam
 - 4) Overall Mulling Configuration not to Exceed: 96" x 84"