

Legend Series

RADIUS

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

| Direct Glazed | | | | | |
|---------------|-----------------------|-------------------|-------|-------------------|----------------------------|
| Series | Window Type | Performance Level | Size | Performance Grade | Air Infiltration (cfm/ft2) |
| Legend CPVC | Direct Glaze - Radius | Standard | 10856 | LC-PG65-FW | 0.01 |
| Legend CPVC | Direct Glaze - Radius | Standard | 10884 | LC-PG50-FW | 0.10 |

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

| Minimum and Maximum Measurements | | | |
|----------------------------------|----------------------|------------------------|----------------------|
| Minimum Frame Width | Minimum Frame Height | Maximum Frame Width | Maximum Frame Height |
| Radius | | | |
| 10 | 10 | Minimum Leg - 6 | |
| Half Rounds | | | |
| 1-8 | 10 | 9-8 | 4-10 |
| Quarter Round | | | |
| 1-0 | 1-0 | 5-0 | 5-0 |
| Special Shapes | | | |
| Aspect Ratio: 7 to 1 | | | |
| Eyebrow Window | | | |
| 3-0 | 1-0 | Aspect Ratio: < 4 to 1 | |
| Ellipse | | | |
| 3-0 | 1-0* | Aspect Ratio: < 4 to 1 | |

*1-6 is frame width is greater than 36"