

Pinnacle Impact Series

CLAD CASEMENT

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Casement					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Pinnacle Clad	Casement Crank-Out	Impact	2668	LC-PG65-C	0.1
Pinnacle Clad	Casement Crank-Out	Impact	3268	LC-PG50-C	0.08

Fixed Casement (Stationary, Picture, Transom)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Pinnacle Clad	Casement Fixed	Impact	4468	LC-PG65-FW	0.1

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Operating			
1-4	1-6	3-0	6-0
Stationary / Picture / Transom			
1-6	1-0	6-0	6-0