

Next Dimension Pro Series

FIXED - STANDARD FRAME

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Fixed					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Pro Std Vinyl	Direct Glaze	Standard	4254	R-PG50-FW	0.10
ND Pro Std Vinyl	Direct Glaze	Standard	7278	R-PG35-FW	0.05

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
Operating			
1-0	1-0	9-2*	6-8*
*Maximum sq.ft. 4'-0"			

Next Dimension Pro Series

FIXED - BRICKMOULD FRAME

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Fixed					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
ND Pro BM Vinyl	Direct Glaze	Standard	9660	R-PG35-FW	0.03
ND Pro BM Vinyl	Direct Glaze	Standard	7278	LC-PG40-FW	0.10

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
Operating			
1-0	1-0	9-2*	6-8*
*Maximum sq.ft. 4'-0"			