

# Revive Series

## HYBRID CASEMENT

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Casement					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Revive Hybrid	Casement Crank-Out	Standard	36" x 72"	LC-PG30-C	0.1
Revive Hybrid	Casement Crank-Out	Standard	28" x 78"	LC-PG35-C	0.08

Fixed Casement (Stationary, Picture, Transom)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Revive Hybrid	Casement Fixed	Standard	72" x 78"	CW-PG40-FW	0.03

**Notes:**

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
<b>Operating</b>			
1-4	1-6	3-0*	6-6**
<b>Stationary / Picture / Transom</b>			
1-6	1-0	6-0	6-6

\*Up to 6'-0" frame height

\*\*Up to 2'-4" frame width