

Legend Series

DOUBLE HUNG

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Double Hung (EZ-Tilt)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Legend CPVC	Double-Hung	Standard	3636	R-PG35-H	0.18
Legend CPVC	Double-Hung	DP Upgrade	3234	R-PG50-H	0.2

Fixed Double Hung (Stationary, Picture, Transom)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Legend CPVC	Double-Hung Picture	Standard	5670	R-PG35-FW	0.10
Legend CPVC	Double-Hung Picture	DP Upgrade	4470	R-PG50-FW	0.10

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Operating			
1-9 3/8	2-8 3/4	3-9 3/8	6-8 3/4
Picture			
1-1 3/8	2-10 3/4	6-1 3/8	6-4 3/4
Transom			
1-9 3/8	1-1 9/16	6-1 3/8	3-1 9/16

Legend Series

DOUBLE HUNG

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Double Hung (Non-EZ Tilt)					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Legend CPVC	Double-Hung Non-EZ Tilt	Standard	3636	LC-PG30-H	0.17

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Operating			
1-9 3/8	2-8 3/4	3-9 3/8	6-8 3/4