

Pinnacle Series

CLAD DIRECT SET

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

| Direct Glazed | | | | | |
|---------------|-------------|-------------------|-------|-------------------|----------------------------|
| Series | Window Type | Performance Level | Size | Performance Grade | Air Infiltration (cfm/ft2) |
| Pinnacle Clad | Direct Set | Standard | 4872 | R-PG70-FW | 0.01 |
| Pinnacle Clad | Direct Set | Standard | 10260 | LC-PG65-FW | 0.01 |
| Pinnacle Clad | Direct Set | Standard | 10283 | CW-PG50-FW | 0.01 |
| Pinnacle Clad | Direct Set | Standard | 12072 | LC-PG50-FW | 0.10 |

Notes:

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

| Minimum and Maximum Measurements | | | |
|----------------------------------|----------------------|---------------------|----------------------|
| Minimum Frame Width | Minimum Frame Height | Maximum Frame Width | Maximum Frame Height |
| Standard | | | |
| 1-2* | 1-2* | 11-11* | 11-11* |

*5 1/2" pitch or 22 degrees

**Frame dimension can not exceed 85" in both directions; Aspect ratio 7 to 1